

Paloma PH-26— External Continuous Flow Gas Water Heater

All new technology: the 26 litres per minute EcoMax!
More features, more flexibility and the performance you expect from Paloma!

- New Look
- New Features
- A New Standard in Continuous Flow Water Heating



FEATURES

- **Hot water on demand** – hot water that never runs out
- **Super efficient** – 6 star energy rating
- **External model** – sleek new design with concealed screws and modern colour
- **Continuous hot water delivery at 26 l/min** – ideal for larger homes and families
- **Digital OK monitor**—shows the temperature when running and for easy fault diagnosis
- **Paloma EZ Link System ready** – delivers up to 52 l/min
- **Improved hot water delivery**—improved flow for cold start up while saving water
- **You're in control** – remote temperature controllers to set the exact temperature you need
- **Available for LPG or Natural Gas**
- **10 Year Heat Exchanger Warranty**

Model	PH – 26
Capacity	26 l/m @ 25' rise
Gas Consumption (min-max)	LPG 0.3—3.9 kg/hr NG 12—199 MJ/hr
Electric Consumption (w)	59 @ 240V
Dimensions (H x W x D)	530 x 350 x 194mm
Weight (kg)	16.0
Minimum flow rate	1.5 l/min
Maximum flow rate	32 l/min
Minimum Water Pressure	120 kPa
Maximum Water Pressure	1000 kPa
Gas & Water Connections	¾ " or 20mm
Safety and efficiency	Auto ignition, temperature controllers, 6* Energy Rating, Frost Protection, EZ Link compatible
Usage	Domestic and Commercial

Hot Water Flow Rate at 25°C Rise	20 l/min External	26l/min Eco External	27l/min Internal	40l/min External EZ Link Unit	52l/min Eco External EZ Link Unit	54l/min Internal EZ link Unit
No of Taps	1-2 Bathrooms 1 Kitchen	2-3 Bathrooms 1 Kitchen	3-4 Bathrooms 1 Kitchen	2-3 Bathrooms 1-2 kitchens	3-4 Bathrooms 1-2 Kitchens	4-5 bathrooms 2 Kitchens
Application	Domestic Only	Domestic / Commercial	Domestic / Commercial	Domestic Only	Domestic / Commercial	Domestic / Commercial

**EXTERNAL
INSTALLATION**

Paloma®